



PERFORMANCE DATA SHEET

Coldstream Max Filter (CF504W)			
Operating Pressure Range	Rated Capacity	Operating Temperature Range	Rated Flow
10psi - 125psi	3000L	5°C - 70°C	2.5L/min
KLT Filtration Ltd recommend that the Filter/Purifier is changed at least every six months. The purifier should be checked for cleaning every few weeks and cleaned according to the owner's manual.			



BACTERIA

Microbial Contaminant	Influent Challenge	Reduction Requirement (%)	Reduction (%) at 3000L	Reduction (%) at 4500L
Klebsiella terrigena	1.228128x10 ⁶ CFU/L	99.9999	>99.9999	99.9999
Cryptosporidium spp.	1.05220x10 ⁶ oocysts/L	99.9	>99.9	99.9



VIRUS

Viral Contaminant	Influent Challenge	Reduction Requirement (%)	Reduction (%) at 3000L	Reduction (%) at 4500L
Rotavirus spp.	1.210461x10 ⁷ PFU/L	99.99	>99.99	99.99



UNIQUE REPLACEMENT INDICATOR

Testing demonstrates that the filter becomes less effective at micro-organism removal as the ceramic thickness decreases, due to regular cleaning. Many regions require regular cleaning of the filter due to poor water quality. In conventional ceramic water filters, there is no indication when the point is reached where the filter is no longer providing protection against micro-organisms and some chemicals. The Max filter provides a warning indicator where the ceramic colour changes from blue to white. When the white ceramic has been reached, the filter can no longer be relied upon to provide protection against micro-organisms in the water and it is time to replace the filter.



The blue ceramic outer layer contains antimicrobial properties which help the filtration process.

As the filter is cleaned, the blue layer is removed until the white ceramic is exposed, indicating time to change.



HEAVY METALS

Metal Contaminant	Influent Challenge (µg/L)	Allowable Concentration (µg/L)	4000L		5000L		6000L	
			Effluent Concentration (µg/L)	Reduction (%)	Effluent Concentration (µg/L)	Reduction (%)	Effluent Concentration (µg/L)	Reduction (%)
Aluminium	3185.0	500	<1	>99.9	18.4	99.4	24.4	99.2
Antimony	6.1	6	<1	>99.9	<1	>99.9	<1	>99.9
Arsenic (3+)	51.5	10	5.4	89.5	10.2	80.2	11.2	78.3
Arsenic (5+)	50.2	10	3.1	93.8	8.7	82.7	10.8	78.5
Barium	10150.0	2000	5.4	>99.9	14.7	99.9	28.6	99.7
Beryllium	50.3	4	<1	>99.9	<1	>99.9	<1	>99.9
Bismuth	50.2	100	<1	>99.9	<1	>99.9	<1	>99.9
Cadmium	30.2	5	<1	>99.9	<1	>99.9	<1	>99.9

MAX

CERAMIC WATER PURIFIER

CF504W

Testing performed under NSF/ANSI standards 42, 53 and P231 by IAPMO R&T Laboratory (NJ), New Jersey USA, EPA ID # NJ01298 NJ DEP ID # 03048 IAPMO ID #102, in compliance with all requirements set forth in N.J.A.C. 7:9E and N.J.A.C. 7:18. Their laboratory is in compliance with all laboratory certification, quality control procedures and requirements as set forth in N.J.A.C. 7:18; the NYCRR Subpart 55-2, the National Environmental Laboratory Accreditation Conference (NELAC) Institute Standards and the ISO 17025.

The purifier has been tested using a Coldstream System to NSF/ANSI standards 42, 53 and P231 for the reduction of the substances listed.

The concentration reduction of substances in the water was reduced to less than or equal to the limit for water leaving the system as specified in NSF/ANSI standards 42, 53 and P231.



PHARMACEUTICALS CONT.

Pharmaceutical Contaminant	Influent Challenge (ng/L)	4000L		5000L		6000L	
		Effluent Concentration (ng/L)	Reduction (%)	Effluent Concentration (ng/L)	Reduction (%)	Effluent Concentration (ng/L)	Reduction (%)
Primidone	1.97	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
Carbamazepine	1.43	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
Testosterone	1.44	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
Progesterone	2.08	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
4-tert-Octylphenol	2.05	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
17-alpha-Ethinylestradiol	2.14	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9
4-para-Nonylphenol	2.28	<0.02	>99.9	<0.02	>99.9	<0.02	>99.9



PARTICLES

99.9% removal of particle reduction class 1, including microplastics.

TESTING INFORMATION



Purifier is only to be used with cold water.



Purifier usage must comply with all state and local laws.



Testing was performed under standard laboratory conditions, actual performance may vary.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



See owner's manual for general installation conditions and needs, plus manufacturer's limited warranty.



This water purifier is not intended to convert waste water or raw sewage into drinking water.

- All contaminants reduced by this purifier are listed.
- Not all contaminants listed may be present in your water.

IAPMO R&T Laboratory (NJ)

Independently Tested and Certified

by IAPMO R&T Laboratory (NJ)

Coldstream® Filters are independently tested and certified to the following:
 NSF/ANSI 42 Aesthetic Effects
 NSF/ANSI 53 Health Effects
 NSF - P231 Microbiological Water Purifiers
 See KLT Filtration Ltd lab reports for more detail

GOLD SEAL CERTIFIED



Manufactured by: KLT Filtration Ltd, Estuary Road, King's Lynn, Norfolk, PE30 2HS, UK.

+44 1553 622000